

TMS Europe Ltd, Unit 10, Stretfield Mill, Bradwell, Hope Valley, S33 9.IT Tel: 01433 620535
Fax: 01433 621492
Email: sales@tmseurope.co.uk
Web www.tmseurope.co.uk
www.tmswebshop.co.uk



TW163 Portable Thermocouple Welder

TMS Europe's TW163 is a capacitance discharge welder designed primarily for thermocouple welding.

It is small and lightweight enough to be carried and used by engineers anywhere on a plant, including confined spaces or with only one hand free.

The welder can run off of its internal battery or the mains, making it suitable for use on-site or in the workshop to weld fine wire thermocouples junctions up to 1mm diameter.

As well as welding fine wire thermocouple junctions, it can also weld thermocouple junctions onto metal bodies for surface temperature measurement. Such applications include thermal surveys of autoclaves, ovens, furnaces and HVAC systems.

- Manual and Auto (Hands free) operation.
- Mains powered or portable battery operation. Unit can operate from Mains supply while recharging battery.
- Variable energy level from 18 to 40 Joules.
- Low Battery LED shows when the battery needs re-charging. Very low battery inhibits operation.
- Auto switch-off to conserve battery.
- Rugged metal case, includes shoulder strap and tool storage.

Energy Output: 18 – 40J

Dimensions: 300 x 190 x 100mm (WxHxD)

Weight: 4.5kg (approx.)

Supply Voltage: 230V UK version; 200 - 260Vac 50Hz, <250W, BS1363 3-pin 13A style UK plug

230V EU version; 200 - 260Vac 50Hz, <250W, CEE 7/7 3-pin 'Schuko' EU plug 115V version; 100 - 130Vac 50/60Hz, <250W, IEC60309 yellow round 16A plug

Battery: Built-in, re-charge time: 6 - 8 hours

Warranty: 2 years return to base warranty against manufacturing defects.

Order Codes: WELD-TW163VM 230V UK version, stocked

WELD-TW163VM-EU 230V EU version, built when ordered WELD-TW163VM-110V 115V version, built when ordered



TMS Europe Ltd was established in 1979 and has designed and manufactured thermocouple welders in the UK since 2001.





Included Accessories

Small Carbon Holder with 4mm plug Short Carbon Electrodes (x3) Large Pliers with 4mm plug Magnet electrode with 4mm plug Large Croc Clip with 4mm socket, Red 4mm plug-plug lead, Red 4mm socket-socket adaptor, Red