

PYROSPOT DGE 10N

Pyrometers for industry and research

Overview

Digital pyrometers with RS-485 interface



Features

- For temperature measurements between 100 °C and 1200 °C
- Keyboard and display for emissivity and temperature
- Temperature linear output 0/4 to 20 mA
- Aiming: aiming light, through-lens sighting or camera module
- Short response times from 2 ms
- Vario optics

Description and applications

The digital pyrometers PYROSPOT DGE 10N are especially designed for industry and research applications. The devices are suitable for temperature measurement from 100 °C on many different surfaces for example metals, ceramics or graphite.

The solid construction in form of a compact housing with a protection window for optics allows usage even under rough environmental conditions. With a short response time of only 2 ms (t95) these pyrometers are also suitable for fast measuring processes. The vario optics with quartz glass protection window realise measuring field diameters from 1.2 mm.


The integrated LED or laser aiming light or, the alternative through-lens sighting, enables an exact focus on the measurement object. With the optional color video module the alignment of the pyrometers to the target can be monitored visually and the entire process can be recorded and documented.

The temperature linear standard output signal of 0/4 to 20 mA allows easy implementation in existing measurement and control systems. The device is equipped with a galvanically isolated RS-485 interface which allows parameterising and software evaluation even in bus systems.

The emissivity is also adjustable via push-buttons and display directly on the device. All parameters can be easily adjusted to the application by using the convenient parameterizing and evaluation software PYROSOFT Spot.

Typical pyrometer application areas:

Steel industry, metal industry, ceramic industry, kiln engineering, soldering installations



PYROSPOT DGE 10N

Pyrometers for industry and research

Technical data

Type	DGE 10N	DGE 10N
Temperature range	100 °C to 850 °C	150 °C to 1200 °C
Sub temperature range	adjustable within temperature range, minimum span 50 °C	
Spectral range	2.0 µm to 2.6 µm	
Optics	vario optics with quartz glass protection window, measuring fields from 1.2 mm	
Distance ratio	approx. 100 : 1	approx. 200 : 1
Measurement uncertainty ¹	0.5 % of measured value + 2 K	
Reproducibility ¹	0.3 % of measured value + 1 K	
NETD ²	0.5 K ¹	
Response time (t95)	2 ms, adjustable up to 100 s	
Emissivity	0.050 to 1.000, adjustable at the device or via interface	
Storage	minimum and maximum value storage, adjustable via interface	
Output	0/4 to 20 mA, switchable via software, temperature linear, max. burden 500 Ω	
Interface	RS-485 (galvanically isolated), half duplex, baudrate up to 115 kbd, data protocol Modbus RTU	
Aiming	LED aiming light, laser aiming light, through-lens sighting or camera module	
Software	PYROSOFT Spot for Windows®, optional: PYROSOFT Spot Pro	
Parameters	emissivity, response time, temperature unit °C or °F, storage, sub temperature range, adjustable via software and interface	
User controls	emissivity control push-buttons (resolution 0.001, aiming light push-button, display	
Power supply	24 V DC ± 25 %	
Power consumption	max. 1.5 W	
Operating temperature	0 °C to 45 °C	
Storage temperature	-20 °C to 70 °C	
Weight	appr. 520 g	
Dimensions	54 × 54 mm, length 170 mm	
Housing	compact housing with plug connector, display, push-buttons and optics protection window	
Safety class	IP 65 (DIN 40 050)	
CE symbol	according to EU regulations (EN 50 011)	
Scope of delivery	PYROSPOT DGE 10N, mounting screw nut, inspection sheet, manual, PYROSOFT Spot for Windows® (without connection cable, please order separately)	

¹T₀ = 23 °C, ε = 1, t95 = 1 s. ² Noise equivalent temperature difference.

Dimensional drawing pyrometer (with through-lens sighting)




PYROSPOT DGE 10N

Pyrometers for industry and research

Vario optics

Measuring distance a [mm]	250	300	350	500	800	4000	Aperture diameter \varnothing D [mm]		Order number	
Optics pullout [mm]	29.2	25.5	23.5	20.3	18.0	15.0	at		LED aiming light	Laser aiming light
Device	Measuring field diameter M [mm]						a = 250 mm	a = 4000 mm	Through-lens sighting	Camera module
DGE 10N (100 °C to 850 °C)	2.5	3.0	3.5	5.0	8.0	40.0	8.0	6.5	5101002222	5101012222
									5101022222	5101032222
DGE 10N (150 °C to 1200 °C)	1.2	1.5	1.7	2.5	4.0	20.0	8.0	6.5	5101002223	5101012223
									5101022223	5101032223

Dimensional drawing vario optics



Detailed view: display

The digital display shows current temperature value and emissivity setting.



Detailed view: back side

The emissivity can be adjusted by using the two keys on the back side of the device. The value settings will be stored automatically.

Through-lens sighting or aiming light push-button

Push-buttons for emissivity adjustment



Plug connector and interface

PYROSPOT DGE 10N

Pyrometers for industry and research

Electrical, mechanical and optical accessories ¹		Order number
Connection cable, 12 pin, angulate plug	length 2 m	3310A11131
	length 5 m	3310A11132
	length 10 m	3310A11133
	length 15 m	3310A11134
	length 20 m	3310A11135
	length 25 m	3310A11136
	length 30 m	3310A11137
Interface module	RS-485 to USB	3310A14020
Power supply PSU 15	24 V DC, 0.6 A	3310A12010
Mounting angle	adjustable	3310A21020
Air purge adaptor	stainless steel, purge air 0.1 to 0,5 bar, oil-free	3310A22020
Window slide	without window	3310A21210
Vacuum flange	KF 16	3310A24015
	with quartz window	3310A34021
	with sapphire window (scratch-proof)	3310A34051
Mounting angle	for cooling jacket	3310A23036
DHP 1040	handheld programming device for parameterizing	3310A17010

¹ More accessories available.

Selected accessories

Mounting angle, adjustable

Order number: 3310A21020



Ball and socket mounting

Order number: 3310A21025



Cooling jacket

Order number: 3310A23031



Cooling plate

Order number: 3310A23020



Air purge unit for cooling jacket

Order number: 3310A22020



Mirror 90°

Order number: 3310A24110



Technical details are subject to change. November 2012.



We are certified for many years according to ISO 9001

Phone: +49 351 871 7228
 Fax: +49 351 871 7230
 E-Mail: info@dias-infrared.de
 Internet: www.dias-infrared.com

DIAS Infrared GmbH
 Gostritzer Straße 65
 01217 Dresden
 Germany